

## **ADECO® FRIZANTIN® -40**

### **Product Description:**

ADECO® FRIZANTIN® -40, is a prepared coolant for cooling systems of motor vehicles, based on monoethylene glycol and special additives packages.

### **Purpose:**

ADECO® FRIZANTIN® -40 is prepared coolant for direct use in cooling and heating system, protects the motor from overheating in summer and freezing in winter. Provides excellent corrosion protection for all metal parts of the cooling system of motor vehicles. It can also be used in either open and closed cooling systems. It can be mixed with other coolants produced on the same basis. Does not contain nitrates, amines and phosphates. It can also be used in other open and closed cooling systems. The recommended replacement period is 2 years or 50,000 km traveled. It can be mixed with other coolants produced on the same basis.

### **The Main Advantages:**

- Excellent freezing protection;
- Excellent protection against corrosion, especially aluminum alloys;
- Good thermal properties;
- Long-term protection;
- Does not create a foam.

### **Physical and Chemical Properties:**

<b><i>Characteristic, Unit</i></b>	<b><i>Referential Values</i></b>	<b><i>Method</i></b>
Density at 20°C, g/cm <sup>3</sup>	1,05 – 1,09	ASTM D 1122
pH value	7 – 9	pH Indicator Strips
Color	blue	Visual
Boiling Point, °C	min 106	ASTM D 1120
Freezing Point, °C	max -37	ASTM D 3321

### **Meet Specifications:**

SRPS H.Z2.010 Tip 3; BS 6580; SAE J1034; ASTM D 3306/4985 Tip 3; AFNOR NF R15-601; VW/Audi/Seat/Škoda/Porsche TL 774-C (G11); MB 325.0; MAN 324 Type NF; BMW N600

**Packaging:** 1 kg, 1 L, 3 L, 60 L, 220 kg, 1000 L