



ADECO® SUPER

Product Description:

ADECO® SUPER is multigrade mineral motor oil, manufactured from specially selected, high quality, selectively and highly refined base oils and additive packages. It is produced in two SAE viscosity grades: 15W-40 and 20W-50.

Purpose:

Multigrade motor oil ADECO® SUPER is produced to meet the requirements for the lubrication of heavy and light diesel engines produced before 1983, as well as gasoline engines produced until 1989, i.e. for the lubrication of gasoline and diesel engines which require oil to meet SF/CD quality level. It is suitable for use under different exploitation conditions and different operation modes.

The Main Advantages:

- Very high engine cleanliness;
- Thermal and oxidation stability;
- Stable oil film;
- Easy engine start.

Physical and Chemical Properties:

Characteristic, Unit	Referential Values		Method
SAE Viscosity Grade	15W-40	20W-50	
Density at 15°C, g/cm ³	0,88 – 0,89	0,89 – 0,91	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	115 – 130	175 – 185	ASTM D 445
Kinematic Viskosity at 100°C, mm ² /s	14 – 15	17 – 19	ASTM D 445
Viscosity Index	120	110	ASTM D 2270
Flash Point, COC, °C	min 235	min 225	ASTM D 92
Pour Point, °C	-15	-10	ASTM D 97
Total Base Number, TBN, mgKOH/g	7	8	ASTM D 2896

Meet Specifications:

API SF/CD; MB 226.1; VW 501.01.

Packaging: 1 L, 4 L, 60 L, 205 L