



ADECO® CHAIN LUBRY SPRAY

Product Description:

Multipurpose lubricant. Contains high viscosity, adhesive oil mixture that provides perfect lubrication for metal parts (chains, bearings, gear wheels, wire ropes, conveyors, etc). Resists extreme pressure (EP) conditions, weak acids and bases. Prevents rusting, creates water and heat resistant layer (from - 30°C to 160°C).

Extremely flammable aerosol.
Pressure container, may burst if heated.

Purpose:

Applicable for the lubrication of both normal and "O" ring chains. Before application clean the surface properly, remove dirty oil and grease. Special spraying head and tube provides precise application.

The Main Advantages:

- exceptional adhesion to surfaces
- prolongs the maintenance cycle by forming a protective layer after lubrication.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Form	Aerosol	Visually
Color	Light amber	Visually
Odor	Specific.	Organoleptic
Solubility in water	Not miscible	-
<i>Petrol (fuel oil), hydrogenated heavy:</i>		
Density at 15°C, g/cm ³	0,817	ASTM D 1298
Viscosity, mm ² /s	<1	ASTM D 445
Melting point, °C	<-66	ASTM D 97
Flash point, °C	47	ASTM D 92
VOC (1999/13/EC), %	68,98	-

Packaging: Spray 500 ml