



# ADECO® MULTI GREASE SPRAY

### **Product Description:**

Contains lithium based universal lubricant grease with excellent adhesion. Creates water repellent, pH neutral layer that resists weather influences, weak acids and bases.

**Extremely flammable aerosol.**  
**Pressure container, may burst if heated.**

### **Purpose:**

Protects metal parts from wear and sticking. Use it for the treatment of chassis parts, hinges, screws and other construction works. Heat resistant from – 30 °C to 160° C. Special spraying head and tube provides precise application.

### **The Main Advantages:**

- exceptional adhesion to surfaces
- prolongs the maintenance cycle by forming a protective layer after lubrication.

### **Physical and Chemical Properties:**

<b><i>Characteristic, Unit</i></b>	<b><i>Referential Values</i></b>	<b><i>Method</i></b>
Form	Aerosol	Visually
Color	Light amber	Visually
Odor	Specific.	Organoleptic
Solubility in water	Not miscible	-
<b><i>Petrol (fuel oil), hydrogenated heavy:</i></b>		
Density at 15°C, g/cm <sup>3</sup>	0,817	ASTM D 1298
Viscosity, mm <sup>2</sup> /s	<1	ASTM D 445
Melting point, °C	<-66	ASTM D 97
Flash point, °C	47	ASTM D 92
VOC ( 1999/13/EC), %	68,98	-

**Packaging:** Spray 500 ml